

## CPH Conch Plastic Camera

EXTRA  
CHEAP

DOME CAMERA

**AHD**  
Analog 1280 × 720P
**Product:**

Analog High Definition conch plastic color camera

24 Pieces LED, 25meters IR distance, DC12V input

**Features:**

- Zn-Al alloy housing with lightweight and convenient
- Anti-electromagnetic interference, excellent video output
- Low illumination, don't need LED compensation infrared
- Low power consumption, wide temperature working
- Easy installation, vehicle cabin ceiling type or flush mount

**Application:**

- Unscrew the pedestal, screws mounting the pedestal on the location of the reservation
- Cable hidden in the vehicle body hole from the pedestal middle hole, or from side hole of the pedestal
- Power on, adjust the camera until the output image appears appropriate scene
- Locking the two ring fixed the camera ball body, the camera installed

Camera video surveillance for commercial vehicle:



Public Transit



School Bus



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Avoid Sunshine



Stabilize Power



Temp Humidity



No Dismantle

**Specifications:**



| Model                  | AC-7AP-CPHR   | AC-1HP-CPHR                         |
|------------------------|---|-------------------------------------|
| CCD or CMOS            | 1/3" Sony HAD II CCD  | 1/3" CMOS 720P                      |
| Resolution             | 700 TVL   | 1.30 Mega Pixel                     |
| Effective Pixels       | PAL: 960Hx720V<br>NTSC: 960Hx612V   | PAL: 1280Hx960V<br>NTSC: 1280Hx720V |
| TV System              | PAL / NTSC (Optional Before Factory)  |                                     |
| Auto Control           | Auto Gain Control, Back Light Compensation<br>White Balance, Electronic Shutter |                                     |
| Image Mirror           | Optional Before Factory   |                                     |
| Lens                   | f=3.6mm View Angle 75degree<br>Optional 2.8, 6mm                                |                                     |
| Light Sensitivity      | 0 Lux @ F1.2 (IR ON)  |                                     |
| Infrared Spectrum      | 850nm or 940 nm   |                                     |
| Infrared LED Range     | 24 LEDs Ø5 IR 25 Meters   |                                     |
| Auto IR control        | 3~5 Lux Cut   |                                     |
| Signal to Noise Ratio  | SNR>50 dB, (AGC Close)  |                                     |
| Video Output           | 1V p-p, 75Ω,  |                                     |
| Audio Output           | <b>Paid Optional Audio, No waterproof</b>                                       |                                     |
| Power Consumption      | 12V DC ± 5%, 135mA, 1.6W  |                                     |
| A / V, Power Interface | Aviation, 4PIN Interface Optional   |                                     |
| Adjustment             | Horizontal 0~360, Vertical 0~90   |                                     |
| Dimensions             | (Φ x H) 94 x H 65 (mm)  |                                     |
| Packing Size           | (L x W x H) 100 x 100 x 100 mm  |                                     |
| Product Weight         | Net: 105 g, All: 135 g  |                                     |
| Waterproof             | IP65 For Housing  |                                     |
| Operating Condition    | Temp.: -25°C to +55°C, Humidity<95%   |                                     |
| Housing Color          | Black, Optional Color By Order Quantity   |                                     |

➤ Specifications are subject to change without prior notice

**Packing List:**

|                     |   |
|---------------------|---|
| Camera              | 1 |
| Instruction manual  | 1 |
| Self-Drilling Screw | 3 |
| Mounting Plug       | 3 |

**Connection:**



**Product Size:**



**Installation Holes:**

