

## Flank View Lizard Camera

BIG  
SALE

## FLANK CAMERA

**AHD**  
Analog 1280 × 720P
**Product:**

Analog High Definition prevent violent destruction flank view lizard camera

10 Pieces LED, 10 meters IR distance, DC12V input

**Features:**

- Plastic toughened housing with common waterproof
- Anti-electromagnetic interference, excellent video output
- High quality IR LED, no infrared lead exposure facula
- Low power consumption, wide temperature working
- Easy installation, vehicle flank surface or flush mount

**Application:**

- Twist off 4 screws on top sides, camera cable through the hole from the pedestal
- Screws mounting the pedestal, top cover with camera body by screws limited on the pedestal
- Power on, adjust the camera until the output image appears appropriate scene, locking screws on top
- Cable hidden in the body and opening waterproofing, the camera installed

Camera video surveillance for commercial vehicle:

**Public Transit****School Bus****Cargo Truck****Sedan SUV**

Please ensure that the product work in the appropriate environment

**Avoid Sunshine****Stabilize Power****Temp Humidity****No Dismantle**



**Specifications:**

Model	AC-7AP-FLHR	AC-1HP-FLHR
CCD or CMOS	1/3" Sony HAD II CCD	1/3" CMOS 720P
Resolution	700 TVL	1.30 Mega Pixel
Effective Pixels	PAL: 960Hx720V NTSC: 960Hx612V	PAL: 1280Hx960V NTSC: 1280Hx720V
TV System	PAL / NTSC (Optional Before Factory)	
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter	
Image Mirror	Optional Before Factory	
Lens	f=2.8mm View Angle 89degree Optional 3.6, 6, 8 mm	
Light Sensitivity	0 Lux @ F1.2 (IR ON)	
Infrared Spectrum	850nm or 940 nm	
Infrared LED Range	10 LEDs Ø5 IR 12 Meters	
Auto IR control	3~5 Lux Cut	
Signal to Noise Ratio	SNR>50 dB, (AGC Close)	
Video Output	1V p-p, 75Ω,	
Audio Output	Null	
Power Consumption	12V DC ± 5%, 100mA, 1.2W	
A / V, Power Interface	Aviation, 4PIN Interface Optional	
Adjustment	Horizontal 0, Vertical 0~60	
Dimensions	(L x W x H) 86 x 64 x 58 mm	
Packing Size	(L x W x H) 85 x 100 x 85 mm	
Product Weight	Net: 165 g, All: 185 g	
Waterproof	IP67 For Housing	
Operating Condition	Temp.: -25°C to +55°C, Humidity < 95%	
Housing Color	Black, Optional Color By Order Quantity	

➤ Specifications are subject to change without prior notice

**Packing List:**

Camera	1
Instruction manual	1
Self-Drilling Screw	4
Mounting Plug	4

**Connection:****Product Size:****Installation Holes:**