

Flank View Upward Camera

TOP
10

REAR CAMERA



Product:

Analog High Definition prevent violent destruction compact flank view upward camera

10 Pieces LED, 10 meters IR distance, DC12V input

Features:

- Lock on vehicle side wall or strap on the bracket of rear view mirror
- Zn-Al alloy housing with better waterproof and prevent violence
- Anti-electromagnetic interference, excellent video output
- High quality IR LED, no infrared lead exposure facula
- Disassembly design, use the special inner hexagon screw the machine

Application:

- Twist off screws on both sides from the bracket, fix the bracket in the mounting position
- Link the cable of the camera through the bracket hole, screw up the screws on the both side
- Power on, adjust the camera until the output image appears appropriate scene, locking screws on both
- Cable hidden in the body and opening waterproofing, the camera installed

Camera video surveillance for commercial vehicle:



Public Transit



School Bus



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Stabilize Power



Temp Humidity



Avoid Sunshine



No Dismantle



Specifications:

Model	AC-0HP-FNHR	AC-1HP-FNHR	AC-2HP-FNHR
CCD or CMOS	1/4" CMOS 720P	1/3" CMOS 960P	1/3" CMOS 1080P
Resolution	1.00 Mega Pixel	1.30 Mega Pixel	2.00 Mega Pixel
Effective Pixels	1280Hx720V	1280Hx960V	1920Hx1080V
TV System	PAL / NTSC (Optional Before Factory)		
Auto Control	Auto Gain Control, Back Light Compensation, White Balance, Electronic Shutter		
Image Mirror	Optional Before Factory		
Lens	f=3.6mm Default, View Angle 75degree, Optional 2.8, 6.0mm		
Light Sensitivity	0 Lux @ F1.2 (IR ON)		
Infrared Spectrum	850nm		
Infrared LED Range	10 LEDs Ø5 IR 10 Meters		
Auto IR control	3~5 Lux Cut		
Signal to Noise Ratio	SNR>50 dB, (AGC Close)		
Video Output	1V p-p, 75Ω		
Audio Output	Null		
Power Consumption	DC12V±5%,95mA,1.1W	DC12V±5%, 110mA, 1.3W	
A / V, Power Interface	Aviation, 4PIN Interface Optional		
Adjustment	Horizontal 0, Vertical 0~22		
Dimensions	(L x W x H) 88 x 70 x 61 mm		
Packing Size	(L x W x H) 100 x 100 x 90 mm		
Product Weight	Net: 295 g, All: 405 g		
Protection level	Waterproof IP68, Vandal-proof IK69 For Housing		
Operating Condition	Temp.: -45°C to +75°C, Humidity<95%		
Housing Color	Black Default, Optional Color By Order Quantity		

➤ Specifications are subject to change without prior notice

Packing List:

Camera	1
Instruction Manual	1
Fixed Collar	1
M6x30mm Hexagon Socket Screw	2

Connection:**Product Size:**