

**Rear View Overlook Camera**

**PRO MODEL**



REAR CAMERA

**AHD**  
Analog 1280 X 720P

**IP68**



**Product:**

Slant bracket for easy installation, don't need to remove the bracket during installation

18 Pieces LED, 15meters IR distance, DC12V input

**Features:**

- Zn-Al alloy housing with better waterproof and prevent violence
- Anti-electromagnetic interference, excellent video output
- High quality IR LED, no infrared lead exposure facula
- Low power consumption, wide temperature working
- Easy installation, vehicle rear surface

**Application:**

- Select installation location, mounting the 2 screws in the front
- Make the 2 screws through the hole on bracket, move the machine back, locking the rear 2 screws
- Power on, adjust the camera until the output image appears appropriate scene, locking screws on both
- Cable hidden in the body and opening waterproofing, the camera installed

Camera video surveillance for commercial vehicle:



**Public Transit**



**School Bus**



**Cargo Truck**



**Sedan SUV**

Please ensure that the product work in the appropriate environment



**Avoid Sunshine**



**Stabilize Power**



**Temp Humidity**



**No Dismantle**

## Specifications:



Model	AC-7AP-ROHR	AC-1HP-ROHR
CCD or CMOS	1/3" Sony HAD II CCD	1/3" CMOS 720P
Resolution	700 TVL	1.30 Mega Pixel
Effective Pixels	PAL: 960Hx720V NTSC: 960Hx612V	PAL: 1280Hx960V NTSC: 1280Hx720V
TV System	PAL / NTSC (Optional Before Factory)	
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter	
Image Mirror	Optional Before Factory	
Lens	f=3.6mm View Angle 75degree Optional 2.8, 6, 8mm	
Light Sensitivity	0 Lux @ F1.2 (IR ON)	
Infrared Spectrum	850nm or 940 nm	
Infrared LED Range	18LEDs Ø5 IR 15 Meters	
Auto IR control	3~5 Lux Cut	
Signal to Noise Ratio	SNR>50 dB, (AGC Close)	
Video Output	1V p-p, 75Ω,	
Audio Output	Paid Optional Audio	
Power Consumption	12V DC ± 5%, 100mA, 1.2W	
A / V, Power Interface	Aviation, 4PIN Interface Optional	
Adjustment	Horizontal 0~45, Vertical 0~90	
Dimensions	(L x W x H) 85 x 75 x 65 mm	
Packing Size	(L x W x H) 85 x 100 x 85 mm	
Product Weight	Net: 315 g, All: 435 g	
Waterproof	IP68 For Housing	
Operating Condition	Temp.: -25°C to +55°C, Humidity<95%	
Housing Color	Black, Optional Color By Order Quantity	

➤ Specifications are subject to change without prior notice

## Packing List:

Camera	1
Instruction manual	1
Self-Drilling Screw	2
Mounting Plug	2

## Connection:



## Product Size:



## Installation Holes:

