MDVR

**CAMERA** 

**ACCESSORY** 

www.zaxbefore.com

## **Rear View Projector Camera**



# **REAR CAMERA**







### **Product:**

Analog High Definition mini infrared rear view projector color camera

12 Pieces LED, 15meters IR distance, DC12V input

#### Features:

- > Zn-Al alloy housing with better waterproof and prevent violence
- > Anti-electromagnetic interference, excellent video output
- ➤ High quality IR LED, no infrared lead exposure facula
- > Low power consumption, wide temperature working
- > Easy installation, vehicle rear surface or vehicle cabin

#### **Application:**

- > Twist off screws on both sides, camera cable through the hole from the bracket
- > Screws mounting the bracket, sunshield and camera body with screws limited on both sides
- > Power on, adjust the camera until the output image appears appropriate scene, locking screws on both
- Cable hidden in the body and opening waterproofing, the camera installed

Camera video surveillance for commercial vehicle:



**Public Transit** 



**School Bus** 



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Avoid Sunshine



**Stabilize Power** 



Temp Humidity



No Dismantle



# Specifications:

Model	AC-7AP-RPHR	AC-1HP-RPHR
CCD or CMOS	1/3"Sony HAD II CCD	1/3"CMOS 720P
Resolution	700 TVL	1.30 Mega Pixel
Effective Pixels	PAL: 960Hx720V NTSC: 960Hx612V	PAL: 1280Hx960V NTSC: 1280H×720V
TV System	PAL / NTSC (Optional Before Factory)	
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter	
Image Mirror	Optional Before Factory	
Lens	f=3.6mm View Angle 75degree Optional 2.8, 6, 8mm	
Light Sensitivity	0 Lux @ F1.2 (IR ON)	
Infrared Spectrum	850nm or 940 nm	
Infrared LED Range	12LEDs Ø5 IR 15 Meters	
Auto IR control	3~5 Lux Cut	
Signal to Noise Ratio	SNR>50 dB, (AGC Close)	
Video Output	1V p-p, 75Ω,	
Audio Output	Paid Optional Audio	
Power Consumption	12V DC $\pm$ 5%, 80mA, 1.0W	
A / V, Power Interface	Aviation, 4PIN Interface Optional	
Adjustment	Horizontal 0~45, Vertical 0~90	
Dimensions	(L x W x H) 48.5 x 87 x 61.5 mm	
Packing Size	(L x W x H) 85 x 100 x 85 mm	
Product Weight	Net: 242 g, All: 335 g	
Waterproof	IP67 For Housing	
Operating Condition	Temp.:-25°C to +55°C, Humidity<95%	
Housing Color	Black, Optional Color By Order Quantity	

> Specifications are subject to change without prior notice


# Packing List:


Camera	1
Instruction manual	1
Self-Drilling Screw	2
Mounting Plug	2

#### **Product Size:**



### Connection:





## **Installation Holes:**

