

### **REAR CAMERA**

www.zaxbefore.com









#### **Product:**

Analog High Definition prevent violent destruction rear view monkey camera

10 Pieces LED, 10meters IR distance, DC12V input

#### Features:

- > Zn-Al alloy camera housing with better CVBS plastic integration support
- Anti-electromagnetic interference, excellent video output
- > High quality IR LED, no infrared lead exposure facula
- > Low power consumption, wide temperature working
- > Easy installation, vehicle rear surface

## Application:

- > Twist off screws on both sides, camera cable through the hole from the bracket
- Screws mounting the bracket, sunshield and camera body with screws limited on both sides
- Power on, adjust the camera until the output image appears appropriate scene, locking screws on both
- Cable hidden in the body and opening waterproofing, the camera installed

Camera video surveillance for commercial vehicle:



Please ensure that the product work in the appropriate environment





## Specifications:


Model	AC-0HP-RSHR	AC-1HP-RSHR	AC-2HP-RSHR
CCD or CMOS	1/3"CMOS 720P	1/3"CMOS 960P	1/3"CMOS 1080P
Resolution	1.00 Mega Pixel	1.30 Mega Pixel	2.00 Mega Pixel
Effective Pixels	1280Hx720V	1280Hx960V	1920Hx1080V
TV System	PAL / NTSC (Optional Before Factory)		
Auto Control	Auto Gain Control, Back Light Compensation, White Balance, Electronic Shutter		
Image Mirror	Optional Before Factory		
Lens	f=3.6mm Default, View Angle 75degree, Optional 2.8, 6.0mm		
Light Sensitivity	0 Lux @ F1.2 (IR ON)		
Infrared Spectrum	850nm		
Infrared LED Range	10LEDs Ø5 IR 10 Meters		
Auto IR control	3~5 Lux Cut		
Signal to Noise Ratio	SNR>50 dB, (AGC Close)		
Video Output	1V p-p, 75Ω,		
Audio Output	Null		
Power Consumption	DC12V±5%,125mA,1.5W DC12V±5%, 140mA, 1.6W		
A / V, Power Interface	Aviation, 4PIN Interface Optional		
Adjustment	Horizontal 0, Vertical 0~90		
Dimensions	(L x W x H) 210 x 133 x 78 mm		
Packing Size	(L x W x H) 250 x 150 x 120 mm		
Product Weight	Net: 250 g, All: 385 g		
Waterproof	IP67 For Housing		
Operating Condition	Temp.:-45°C to +75°C, Humidity<95%		
Housing Color	Black Default, Optional Color By Order Quantity		


# > Specifications are subject to change without prior notice

# **Packing List:**

Camera	1
Instruction manual	1
Self-Drilling Screw	2
Mounting Plug	2

# Connection:





### **Product Size:**



