Snail Jar Camera





MINI DOME CAMERA









Product:

Analog High Definition mini dome snail jar color camera

12 Pieces LED, 10 meters IR distance, DC12V input

Features:

- Zn-Al alloy housing with lightweight and convenient
- Anti-electromagnetic interference, excellent video output
- > High quality IR LED, no infrared lead exposure facula
- Low power consumption, wide temperature working
- > Easy installation, vehicle cabin ceiling type or flush mount

Application:

- Unscrew the pedestal, screws mounting the pedestal on the location of the reservation.
- > Cable hidden in the vehicle body hole from the pedestal middle hole, or from side hole of the pedestal
- Power on, adjust the camera until the output image appears appropriate scene
- Locking the two ring fixed the camera ball body, the camera installed

Camera video surveillance for commercial vehicle:









School Bus

Cargo Truck

Sedan SUV

Please ensure that the product work in the appropriate environment









Stabilize Power

Temp Humidity

Avoid Sunshine

No Dismantle



CAMERA

MDVR

Specifications:


Model	AC-0HP-SJHR	AC-1HP-SJHR	AC-2HP-SJHR
CCD or CMOS	1/3"CMOS 720P	1/3"CMOS 960P	1/3"CMOS 1080P
Resolution	1.00 Mega Pixel	1.30 Mega Pixel	2.00 Mega Pixel
Effective Pixels	1280Hx720V	1280Hx960V	1920Hx1080V
TV System	PAL / NTSC (Optional Before Factory)		
Auto Control	Auto Gain Control, Back Light Compensation, White Balance, Electronic Shutter		
Image Mirror	Optional Before Factory		
Lens	f=3.6mm Default, View Angle 75degree, Optional 2.8, 6.0mm		
Light Sensitivity	0 Lux @ F1.2 (IR ON)		
Infrared Spectrum	850nm		
Infrared LED Range	12 LEDs Ø5 IR 10 Meters		
Auto IR control	3~5 Lux Cut		
Signal to Noise Ratio	SNR>50 dB, (AGC Close)		
Video Output	1V p-p, 75Ω,		
Audio Output		Null	
Power Consumption	DC12V±5%,150mA,1.8W	DC12V±5%	,165mA,2.0W
A / V, Power Interface	Aviation, 4PIN Interface Optional		
Adjustment	Horizontal 0~360, Vertical 0~90		
Dimensions	(Φ x H) 60 x H 50 (mm)		
Packing Size	(L x W x H) 70 x 70 x 70 mm		
Product Weight	Net: 145 g, All: 190 g		
Waterproof	IP67 For Housing		
Operating Condition	Temp.:-45°C to +75°C, Humidity<95%		
Housing Color	Black Default, Optional Color By Order Quantity		


> Specifications are subject to change without prior notice

Packing List:

Camera	1
Instruction manual	1
Self-Drilling Screw	3
Mounting Plug	3

Connection:





Product Size:



Installation Holes:

