

PRO
MODEL

MINI DOME CAMERA

**Product:**

Analog High Definition mini dome snail khaki color camera

6 Pieces LED, 10 meters IR distance, 5 meters audio pickup, DC12V input

Features:

- Zn-Al alloy housing with lightweight and convenient
- Anti-electromagnetic interference, excellent video output
- High quality IR LED, no infrared lead exposure facula
- Low power consumption, wide temperature working
- Easy installation, vehicle cabin ceiling type or flush mount

Application:

- Unscrew the pedestal, screws mounting the pedestal on the location of the reservation
- Cable hidden in the vehicle body hole from the pedestal middle hole, or from side hole of the pedestal
- Power on, adjust the camera until the output image appears appropriate scene
- Locking the two ring fixed the camera ball body, the camera installed

Camera video surveillance for commercial vehicle:



Public Transit



School Bus



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Stabilize Power



Temp Humidity



Avoid Sunshine



No Dismantle



Specifications:

Model	AC-0HPA-SKHR	AC-1HPA-SKHR	AC-2HPA-SKHR
CCD or CMOS	1/3" CMOS 720P	1/3" CMOS 960P	1/3" CMOS 1080P
Resolution	1.00 Mega Pixel	1.30 Mega Pixel	2.00 Mega Pixel
Effective Pixels	1280Hx720V	1280Hx960V	1920Hx1080V
TV System	PAL / NTSC (Optional Before Factory)		
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter		
Image Mirror	Optional Before Factory		
Lens	f=3.6mm Default, View Angle 75degree, Optional 2.8, 6.0mm		
Light Sensitivity	0 Lux @ F1.2 (IR ON)		
Infrared Spectrum	850nm		
Infrared LED Range	6 LEDs Ø5 IR 10 Meters		
Auto IR control	3~5 Lux Cut		
Signal to Noise Ratio	SNR > 50 dB, (AGC Close)		
Video Output	1V p-p, 75Ω,		
Audio Output	5 Meters Audio Pickup		
Power Consumption	DC12V±5%, 150mA, 1.8W	DC12V±5%, 165mA, 2.0W	
A / V, Power Interface	Aviation, 4PIN Interface Optional		
Adjustment	Horizontal 0~360, Vertical 0~90		
Dimensions	(Φ x H) 68 x H 65 (mm)		
Packing Size	(L x W x H) 100 x 100 x 90 mm		
Product Weight	Net: 145 g, All: 195 g		
Waterproof	Null		
Operating Condition	Temp.: -25°C to +55°C, Humidity < 95%		
Housing Color	Khaki Default, Optional Color By Order Quantity		

➤ Specifications are subject to change without prior notice

Packing List:

Camera	1
Instruction manual	1
Self-Drilling Screw	3
Mounting Plug	3

Connection:**Product Size:****Installation Holes:**