SPH Snail Plastic Camera



ACCESSORY

MINI DOME CAMERA







Product:

Analog High Definition plastic mini snail color camera

12 Pieces LED, 10 meters IR distance, DC12V input

Features:

- Plastic housing with lightweight and convenient
- Image effect more meticulous, excellent video output
- High quality IR LED, no infrared lead exposure facula
- > Low power consumption, wide temperature working
- > Easy installation, vehicle surface or flush mount

Application:

- Unscrew the pedestal, screws mounting the pedestal on the location of the reservation
- Cable hidden in the vehicle body hole from the pedestal middle hole, or from side hole of the pedestal
- > Power on, adjust the camera until the output image appears appropriate scene
- > Locking the two ring fixed the camera ball body, the camera installed

Camera video surveillance for commercial vehicle:



Public Transit



School Bus



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Avoid Sunshine



Stabilize Power



Temp Humidity



No Dismantle



CAMERA

Specifications:

MDVR

Model	AC-7AP-SPHR	AC-1HP-SPHR
CCD or CMOS	1/3"Sony HAD II CCD	1/3"CMOS 720P
Resolution	700 TVL	1.30 Mega Pixel
Effective Pixels	PAL: 960Hx720V NTSC: 960Hx612V	PAL: 1280Hx960V NTSC: 1280Hx720V
TV System	PAL / NTSC (Optional Before Factory)	
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter	
Image Mirror	Optional Before Factory	
Lens	f=3.6mm View Angle 75degree Optional 2.8, 6, 8mm	
Light Sensitivity	0 Lux @ F1.2 (IR ON)	
Infrared Spectrum	850nm or 940 nm	
Infrared LED Range	12 LEDs Ø5 IR 10 Meters	
Auto IR control	3~5 Lux Cut	
Signal to Noise Ratio	SNR>50 dB, (AGC Close)	
Video Output	1V p-p, 75Ω,	
Audio Output	Null	
Power Consumption	12V DC \pm 5%, 100mA, 1.2W	
A / V, Power Interface	Aviation, 4PIN Interface Optional	
Adjustment	Horizontal 0~360, Vertical 0~90	
Dimensions	(Φ x H) 70 x H 50 (mm)	
Packing Size	(L x W x H) 85 x 85 x 60 mm	
Product Weight	Net: 85 g, All: 225 g	
Waterproof	IP65 For Housing	
Operating Condition	Temp.:-25°C to +55°C, Humidity<95%	
Housing Color	Black, Optional Color By Order Quantity	

> Specifications are subject to change without prior notice

Packing List:

Camera	1
Instruction manual	1
Self-Drilling Screw	3
Mounting Plug	3

Product Size:



Connection:



Installation Holes:



