

Front View Ateles Color Camera

NEW
PRODUCT

PRO TAXI CAMERA

AHD
Analog 1280 x 720P
**Product:**

Analog HD prevent violent destruction taxi front view Ateles low illumination color camera

5 meters Audio pickup, DC12V input

Features:

- Zn-Al alloy housing with better waterproof and prevent violence
- Anti-electromagnetic interference, excellent video output
- High quality audio pickup, the sound revivification driving cabin
- Low power consumption, wide temperature working
- Easy installation, 3M double-sided adhesive or 4 screws fixed

Application:

- Please installation the machine at the middle-upper in vehicle cabin, headspace for the machine cable
- Pasted 3M adhesive on the bracket, then pasted the bracket on the installation place
- Power on, adjust the camera until the image appears appropriate scene, locking screws on both sides
- Cable hidden in the body and opening waterproofing, the camera installed

Camera video surveillance for commercial vehicle:

**Public Transit****School Bus****Cargo Truck****Sedan SUV**

Please ensure that the product work in the appropriate environment

**Avoid Sunshine****Stabilize Power****Temp Humidity****No Dismantle**

Specifications:



| | |
|------------------------|---|
| Model | AC-1HPA-TAH |
| CCD or CMOS | 1/3" CMOS 720P |
| Resolution | 1.30 Mega Pixel |
| Effective Pixels | PAL: 1280Hx960V NTSC: 1280Hx720V |
| TV System | PAL / NTSC (Optional Before Factory) |
| Auto Control | Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter |
| Image Mirror | Optional Before Factory |
| Lens | f=2.4mm View Angle 140 degree Optional 3.6, 6mm |
| Light Sensitivity | 0 Lux @ F1.2 (IR ON) |
| Infrared Spectrum | 850nm or 940 nm |
| Infrared LED Range | NULL |
| Auto IR control | 3~5 Lux Cut |
| Signal to Noise Ratio | SNR>50 dB, (AGC Close) |
| Video Output | 1V p-p, 75Ω, |
| Audio Output | Audio Pickup |
| Power Consumption | 12V DC±5%, 80~95mA, 0.9~1.2W |
| A / V, Power Interface | Aviation, 4PIN Interface Optional |
| Adjustment | Horizontal 0, shift 25mm; Vertical 0~300 |
| Dimensions | (L x W x H) 45 x 43 x 32 mm |
| Packing Size | (L x W x H) 85 x 85 x 60 mm |
| Product Weight | Net: 100 g, All: 160 g |
| Waterproof | NULL |
| Operating Condition | Temp.: -25°C to +55°C, Humidity<95% |
| Housing Color | Black, Optional Color By Order Quantity |

➤ Specifications are subject to change without prior notice

Packing List:

| | |
|-------------------------------------|---|
| Camera | 1 |
| Instruction manual | 1 |
| 3M Double-Sided Adhesive | 1 |
| Self-Drilling Screw & Mounting Plug | 4 |

Connection:



Product Size:

