Front View Ateles Color Camera



ACCESSORY

PRO TAXI CAMERA









Product:

Analog HD prevent violent destruction taxi front view Ateles low illumination color camera

2 Pieces LED, DC12V input

Features:

- Zn-Al alloy housing with better waterproof and prevent violence
- > Anti-electromagnetic interference, excellent video output
- High quality IR LED, no infrared lead exposure facula
- Low power consumption, wide temperature working
- > Easy installation, 3M double-sided adhesive or 4 screws fixed

Application:

- Please installation the machine at the middle-upper in vehicle cabin, headspace for the machine cable
- Pasted 3M adhesive on the bracket, then pasted the bracket on the installation place
- > Power on, adjust the camera until the image appears appropriate scene, locking screws on both sides
- Cable hidden in the body and opening waterproofing, the camera installed

Camera video surveillance for commercial vehicle:



Public Transit



School Bus



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Avoid Sunshine



Stabilize Power



Temp Humidity



No Dismantle



Specifications:


likin.	
Model	AC-1HP-TAHR
CCD or CMOS	1/3"CMOS 720P
Resolution	1.30 Mega Pixel
Effective Pixels	PAL: 1280Hx960V NTSC: 1280H×720V
TV System	PAL / NTSC (Optional Before Factory)
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter
Image Mirror	Optional Before Factory
Lens	f=2.4mm View Angle 140 degree Optional 3.6, 6mm
Light Sensitivity	0 Lux @ F1.2 (IR ON)
Infrared Spectrum	850nm or 940 nm
Infrared LED Range	2 LEDs Ø5 IR 5 Meters
Auto IR control	3~5 Lux Cut
Signal to Noise Ratio	SNR>50 dB, (AGC Close)
Video Output	1V p-p, 75Ω,
Audio Output	Null
Power Consumption	12V DC \pm 5%, 80~95mA, 0.9~1.2W
A / V, Power Interface	Aviation, 4PIN Interface Optional
Adjustment	Horizontal 0, Shift 25mm; Vertical 0~300
Dimensions	(L x W x H) 45 x 43 x 32 mm
Packing Size	(L x W x H) 85 x 85 x 60 mm
Product Weight	Net: 100 g, All: 160 g
Waterproof	Waterproof IP67
Operating Condition	Temp.:-25°C to +55°C, Humidity<95%
Housing Color	Black, Optional Color By Order Quantity


> Specifications are subject to change without prior notice

Packing List:

Camera	
Instruction manual	
3M Double-Sided Adhesive	
Self-Drilling Screw & Mounting Plug	

Connection:





Product Size:

