

Cabin UFO Dome Color Camera

PRO MODEL



UIH



UIHR

CABIN UFO CAMERA



AHD
Analog 1280 x 720P

AC-AH-UIH



PAID BUY



Product:

Analog High Definition prevent violent destruction cabin UFO dome color camera

Optional infrared, Optional tilting bracket, DC12V input

Features:

- Zn-Al alloy housing with better waterproof and prevent violence
- Anti-electromagnetic interference, excellent video output
- High quality IR LED, no infrared lead exposure facula
- Low power consumption, wide temperature working
- Easy installation, 3M double-sided adhesive or 4 screws fixed

Application:

- Twist off screws on upper fixed ring, twist off the upper fixed ring and the dome cover
- 4 screws mounting the machine, or use the tilling bracket, unscrew the camera ball fixed ring
- Power on, adjust the camera until the image appears appropriate scene, locking the camera fixed ring
- Cable hidden in the body and waterproofing, locking screws on upper fixed ring, the camera installed

Camera video surveillance for commercial vehicle:



Public Transit



School Bus



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Avoid Sunshine



Stabilize Power



Temp Humidity



No Dismantle

Specifications:



Model	AC-7AP-UIH	AC-1HP-UIH
CCD or CMOS	1/3" Sony HAD II CCD	1/3" CMOS 720P
Resolution	700 TVL	1.30 Mega Pixel
Effective Pixels	PAL: 960Hx720V NTSC: 960Hx612V	PAL: 1280Hx960V NTSC: 1280Hx720V
TV System	PAL / NTSC (Optional Before Factory)	
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter	
Image Mirror	Optional Before Factory	
Lens	f=3.6mm View Angle 75degree Optional 2.8, 6, 8mm	
Light Sensitivity	0 Lux @ F1.2 (IR ON)	
Infrared Spectrum	Infrared-Sensitive	
Infrared LED Range	Null	
Auto IR control	Null	
Signal to Noise Ratio	SNR>50 dB, (AGC Close)	
Video Output	1V p-p, 75Ω,	
Audio Output	Null	
Power Consumption	12V DC±5%, 80~95mA, 0.9~1.2W	
A / V, Power Interface	Aviation, 4PIN Interface Optional	
Adjustment	Horizontal 0, shift 25mm; Vertical 0~300	
Dimensions	(L x W x H) 45 x 43 x 32 mm	
Packing Size	(L x W x H) 85 x 85 x 60 mm	
Product Weight	Net: 100 g, All: 160 g	
Waterproof	IP65 For Housing	
Operating Condition	Temp.: -25°C to +55°C, Humidity<95%	
Housing Color	Black, Optional Color By Order Quantity	

➤ Specifications are subject to change without prior notice

Packing List:

Camera	1
Instruction manual	1
Self-Drilling Screw	4
Mounting Plug	4

Connection:



Product Size:



Installation Holes:

