

Taxi Front View Beautiful Lip Camera

PRO
MODEL

PRO TAXI CAMERA

AHD
Analog 1280 x 720P

Product:

Analog HD prevent violent destruction taxi front view beautiful lip low illumination color camera

12pcs HQ LED, low power consumption, DC12V input

Features:

- Zn-Al alloy housing with better waterproof and prevent violence
- Anti-electromagnetic interference, excellent video output
- Low illumination, don't need LED compensation infrared
- Low power consumption, wide temperature working
- Easy installation, vehicle surface or flush mount

Application:

- Unscrew the pedestal, screws mounting the pedestal on the location of the reservation
- Cable hidden in the vehicle body hole from the pedestal middle hole, or from side hole of the pedestal
- Power on, adjust the camera until the output image appears appropriate scene
- Locking the outside ring fixed the camera ball body, the camera installed

Camera video surveillance for commercial vehicle:



Public Transit



School Bus



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Avoid Sunshine



Stabilize Power



Temp Humidity



No Dismantle

Specifications:



Model	AC-7AP-TLHR	AC-1HP-TLHR
CCD or CMOS	1/3" Sony HAD II CCD	1/3" CMOS 720P
Resolution	700 TVL	1.30 Mega Pixel
Effective Pixels	PAL: 960Hx720V NTSC: 960Hx612V	PAL: 1280Hx960V NTSC: 1280Hx720V
TV System	PAL / NTSC (Optional Before Factory)	
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter	
Image Mirror	Optional Before Factory	
Lens	f=2.8mm View Angle 89degree Optional 3.6, 6mm	
Light Sensitivity	0 Lux @ F1.2 (IR ON)	
Infrared Spectrum	850nm or 940nm	
Infrared LED Range	12 HQ LEDs Ø3 IR 15 Meters	
Auto IR control	3~5 Lux Cut	
Signal to Noise Ratio	SNR>50 dB, (AGC Close)	
Video Output	1V p-p, 75Ω,	
Audio Output	Null	
Power Consumption	12V DC±5%, 80mA, 0.9W	
A / V, Power Interface	Aviation, 4PIN Interface Optional	
Adjustment	Horizontal 0~360; Vertical 0~90	
Dimensions	(Φ x H) 54 x H 46 (mm)	
Packing Size	(L x W x H) 80 x 80 x 60 mm	
Product Weight	Net: 145 g, All: 265 g	
Waterproof	IP67 For Housing	
Operating Condition	Temp.: -25°C to +55°C, Humidity<95%	
Housing Color	Black, Optional Color By Order Quantity	

➤ Specifications are subject to change without prior notice

Packing List:

Camera	1
Instruction manual	1
3M Double-Sided Adhesive	1
Self-Drilling Screw & Mounting Plug	3

Connection:



Product Size:



Installation Holes:

