

Taxi Front View Tofu Camera

PRO
MODEL

PRO TAXI CAMERA

AHD
Analog 1280 × 720P
**Product:**

Analog HD prevent violent destruction taxi front view tofu low illumination color camera

DC12V input, low power consumption

Features:

- Zn-Al alloy housing with better waterproof and prevent violence
- Anti-electromagnetic interference, excellent video output
- Low illumination, don't need LED compensation infrared
- Low power consumption, wide temperature working
- Easy installation, vehicle surface or flush mount

Application:

- Twist off screws on both sides, camera cable through the hole from the bracket
- Screws mounting the bracket, camera body with screws limited on both sides
- Power on, adjust the camera until the image appears appropriate scene, locking screws on both sides
- Cable hidden in the body and opening waterproofing, the camera installed

Camera video surveillance for commercial vehicle:

**Public Transit****School Bus****Cargo Truck****Sedan SUV**

Please ensure that the product work in the appropriate environment

**Avoid Sunshine****Stabilize Power****Temp Humidity****No Dismantle**

Specifications:



Model	AC-7AP-TTH	AC-1HP-TTH
CCD or CMOS	1/3" Sony HAD II CCD	1/3" CMOS 720P
Resolution	700 TVL	1.30 Mega Pixel
Effective Pixels	PAL: 960Hx720V NTSC: 960Hx612V	PAL: 1280Hx960V NTSC: 1280Hx720V
TV System	PAL / NTSC (Optional Before Factory)	
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter	
Image Mirror	Optional Before Factory	
Lens	f=2.35mm View Angle 130 degree Optional 2.1(160°), 3.6mm	
Light Sensitivity	0.01 Lux @ F1.2	
Infrared Spectrum	Infrared-Sensitive	
Infrared LED Range	Null	
Auto IR control	Null	
Signal to Noise Ratio	SNR>50 dB, (AGC Close)	
Video Output	1V p-p, 75Ω,	
Audio Output	Paid Optional	
Power Consumption	12V DC±5%, 90mA, 1.1W	
A / V, Power Interface	Aviation, 4PIN Interface Optional	
Adjustment	Horizontal 0~45; Vertical 0~90	
Dimensions	(L x W x H) 25 x 24 x 34 mm	
Packing Size	(L x W x H) 80 x 80 x 60 mm	
Product Weight	Net: 55 g, All: 120 g	
Waterproof	Null	
Operating Condition	Temp.: -25°C to +55°C, Humidity<95%	
Housing Color	Black, Optional Color By Order Quantity	

➤ Specifications are subject to change without prior notice




Packing List:

Camera	1
Instruction manual	1
Self-Drilling Screw	1
Mounting Plug	3

Connection:



Product Size:



Installation Holes:

