

Flank View Pug Camera

NEW PRODUCT



FLANK CAMERA



Product:

Analog High Definition prevent violent destruction flank view pug camera

5 Pieces LED, 6 meters IR distance, DC12V input

Features:

- Zn-Al alloy housing with better waterproof and prevent violence
- Anti-electromagnetic interference, excellent video output
- High quality IR LED, no infrared lead exposure facula
- Low power consumption, wide temperature working
- Easy installation, vehicle flank surface or flush mount

Application:

- Twist off 4 screw at the front, put off the bracket, installation the it in the selected location
- Fixation the bracket on the car body use the 3 screws, lock the screw to fix camera
- Connect the cable and power on, adjust the camera until the output image appears appropriate scene
- Cable hidden in the body and opening waterproofing, the camera installed

Camera video surveillance for commercial vehicle:



Public Transit



School Bus



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Avoid Sunshine



Stabilize Power



Temp Humidity



No Dismantle

Specifications:


Model	AC-1HP-FPHR	AC-1HP-FPHR
CCD or CMOS	1/3" CCD	1/3" CMOS 720P
Resolution	420TVL	500TVL
Effective Pixels	PAL: 582Hx512V NTSC: 512Hx492V	PAL: 728Hx488V NTSC: 562Hx420V
TV System	PAL / NTSC Optional Before Factory	
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter	
Image Mirror	Optional Before Factory	
Lens	f=2.2mm View Angle 150degree	
Light Sensitivity	0.1 Lux, 0 Lux @ F1.2 (IR ON)	
Infrared Spectrum	850nm or 940 nm	
Infrared LED Range	5 LEDs Φ5 IR 6 Meters	
Auto IR control	3~5 Lux Cut	
Signal to Noise Ratio	SNR>48 dB, (AGC Close)	
Video Output	1V p-p, 75Ω,	
Audio Output	Null	
Power Consumption	12V DC ± 5%, 80mA, 135mA(IR ON) Max 1.60W	
A / V, Power Interface	Aviation, BMW ICOM Interface Optional	
Adjustment	Horizontal 0, Vertical 0	
Dimensions	(L x W x H) 68 x 56 x 48 mm	
Packing Size	(L x W x H) 100 x 100 x 90 mm	
Product Weight	Net: 150 g, All: 255 g	
Waterproof	IP67 For Housing	
Operating Condition	Temp.: -25°C to +55°C, Humidity<95%	
Housing Color	Black, Optional Color By Order Quantity	

➤ Specifications are subject to change without prior notice


Packing List:

Camera	1
Instruction manual	1
Self-Drilling Screw	3
Mounting Plug	3

Connection:



AVIATION



BMW ICOM

Product Size:



Installation:

