

Front View Ateles Color Camera

NEW
PRODUCT

PRO TAXI CAMERA

AHD
Analog 1280 x 720P
**Product:**

Analog HD prevent violent destruction taxi front view Ateles low illumination color camera

DC12V input

Features:

- Zn-Al alloy housing with better waterproof and prevent violence
- Anti-electromagnetic interference, excellent video output
- Waterproof IP67, without IR LED, without audio pickup
- Low power consumption, wide temperature working
- Easy installation, 3M double-sided adhesive or 4 screws fixed

Application:

- Please installation the machine at the middle-upper in vehicle cabin, headspace for the machine cable
- Pasted 3M adhesive on the bracket, then pasted the bracket on the installation place
- Power on, adjust the camera until the image appears appropriate scene, locking screws on both sides
- Cable hidden in the body and opening waterproofing, the camera installed

Camera video surveillance for commercial vehicle:



Public Transit



School Bus



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Avoid Sunshine



Stabilize Power



Temp Humidity



No Dismantle

Specifications:



Model	AC-1HP-TAH
CCD or CMOS	1/3" CMOS 720P
Resolution	1.30 Mega Pixel
Effective Pixels	PAL: 1280Hx960V NTSC: 1280Hx720V
TV System	PAL / NTSC (Optional Before Factory)
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter
Image Mirror	Optional Before Factory
Lens	f=2.4mm View Angle 140 degree Optional 3.6, 6mm
Light Sensitivity	0 Lux @ F1.2 (IR ON)
Infrared Spectrum	850nm or 940 nm
Infrared LED Range	Null
Auto IR control	3~5 Lux Cut
Signal to Noise Ratio	SNR>50 dB, (AGC Close)
Video Output	1V p-p, 75Ω,
Audio Output	Null
Power Consumption	12V DC±5%, 80~95mA, 0.9~1.2W
A / V, Power Interface	Aviation, 4PIN Interface Optional
Adjustment	Horizontal 0, shift 25mm; Vertical 0~300
Dimensions	(L x W x H) 45 x 43 x 32 mm
Packing Size	(L x W x H) 85 x 85 x 60 mm
Product Weight	Net: 100 g, All: 160 g
Waterproof	IP67 For Housing
Operating Condition	Temp.: -40°C to + 85°C, Humidity<95%
Housing Color	Black, Optional Color By Order Quantity

➤ Specifications are subject to change without prior notice

Packing List:

Camera	1
Instruction manual	1
3M Double-Sided Adhesive	1
Self-Drilling Screw & Mounting Plug	4

Connection:



Product Size:

