

Double Head Eagle Camera



Group Installation



DOUBLE HEAD CAMERA



Split Installation



Product:


Double Head Eagle Camera DHE2, shape design from double-head eagle emblem image, monitor vehicle ahead and inside scene. 10 Pieces LED, 5meters IR distance, DC12V input

Features:


- Ahead Mini vehicle wide view High-definition double cameras
- Cabin camera monitor all passenger and HD voice sync pickup
- Cabin LED adopt the anti-glare infrared,
- Low power consumption, wide temperature working
- Integration install or Fission install, easy installation

Application:

- Product structure introduction:



A—Light sensor
 B—Microphone hole
 C—Wide-angle inside camera
 D—Regulating screw of inside



E—Video, audio, power
 F—Ahead view camera lens

Camera video surveillance for commercial vehicle:



Public Transit



School Bus



Cargo Truck



Sedan SUV

Please ensure that the product work in the appropriate environment



Avoid Sunshine



Stabilize Power



Temp Humidity



No Dismantle

Specifications:



Model	AC-7APA-DFHR	AC-1HPA-DFHR
CCD or CMOS	1/3" Sony HAD II CCD	1/3" CMOS 720P
Resolution	700 TVL	1.30 Mega Pixel
Effective Pixels	PAL: 960Hx720V NTSC: 960Hx612V	PAL: 1280Hx960V NTSC: 1280Hx720V
TV System	PAL / NTSC (Optional Before Factory)	
Auto Control	Auto Gain Control, Back Light Compensation White Balance, Electronic Shutter	
Lens	Ahead Lens 3.7mm, 96° Wide Angle Cabin Lens 2.1mm, 130° Wide Angle	
Light Sensitivity	0 Lux @ F1.2 (IR ON)	
Infrared Spectrum	850nm or 940 nm	
Infrared LED Range	Cabin Camera 10 LEDs Ø8 IR 15 Meters	
Auto IR control	3~5 Lux Cut	
Signal to Noise Ratio	SNR > 50 dB, (AGC Close)	
Video Output	1V p-p, 75Ω,	
Audio Output	Cabin Camera With Voice Pickup	
Power Consumption	Ahead: 12V DC ± 5%, 60mA, 0.5W Cabin: 12V DC ± 5%, 120mA, 1.5W	
A / V, Power Interface	Aviation, 4PIN Interface Optional	
Adjustment	Cabin Horizontal 0~135, Vertical 0~120	
Dimensions	Machine Size (L x W x H) 120 x 125 x 30 mm Ahead Size (L x W x H) 32 x 50 x 30 mm Cabin Size (L x W x H) 88 x 117 x 30 mm	
Packing Size	(L x W x H) 110 x 150 x 45 mm	
Product Weight	Net: 455 g, All: 675 g	
Waterproof	IP65 For Housing	
Operating Condition	Temp.: -25°C to +55°C, Humidity < 95%	
Housing Color	Black, Optional Color By Order Quantity	

➤ Specifications are subject to change without prior notice

Packing List:

Ahead & Cabin Camera	1
Instruction Manual	1
Allen Driver	1
3M Gum	1

Connection:



Product Size:

