

## Product:

SONY CCD 700TVL metallic anti-violence waterproof khaki housing smart infrared color conch camera 24 Pieces LED, 25meters IR distance, DC12V input

## Features:

- Zn-Al alloy housing with lightweight and convenient
- Anti-electromagnetic interference, excellent video output
- > High quality IR LED, no infrared lead exposure facula
- Low power consumption, wide temperature working ≻
- Easy installation, vehicle cabin ceiling type or flush mount

## **Application:**

- Unscrew the pedestal, screws mounting the pedestal on the location of the reservation
- > Cable hidden in the vehicle body hole from the pedestal middle hole, or from side hole of the pedestal
- Power on, adjust the camera until the output image appears appropriate scene
- Locking the two ring fixed the camera ball body, the camera installed

Camera video surveillance for commercial vehicle:







Sedan SUV

Please ensure that the product work in the appropriate environment















**Temp Humidity** 

**Avoid Sunshine** 

**No Dismantle** 



MDVR CAMERA

Model	AC-7AP-CKH	AC-7APA-CKH	AC-7APA-CKHR	
CCD or CMOS	1/3"Sony HAD II CCD			
Resolution	700 TVL			
Effective Pixels		960Hx720V		
TV System	PAL / NTSC (Optional Before Factory)			
Auto Control	Auto Gain Control, Back Light Compensation, White Balance, Electronic Shutter			
Image Mirror	Optional Before Factory			
Lens	f=3.6mm View Angle 75degree, Optional 2.8, 6.0mm			
Light Sensitivity	0 Lux @ F1.2 (IR ON)			
Infrared Spectrum	850nm			
Infrared LED Range	Null 24		24 LEDs Ø5 IR 25 Meters	
Auto IR control	3~5 Lux Cut			
Signal to Noise Ratio	SNR>50 dB, (AGC Close)			
Video Output		1V p-p, 75Ω,		
Audio Output	Null	Audio	o Pickup	
Power Consumption	DC12V±5%,65mA,0.8W DC12V±5%,260mA,		DC12V±5%,260mA,3.2W	
A / V, Power Interface	Aviation, 4PIN Interface Optional			
Adjustment	Horizontal 0~360, Vertical 0~90			
Dimensions	(Φ x H) 97 x H 65 (mm)			
Packing Size	(L x W x H) 100 x 100 x 90 mm			
Product Weight	Net: 225 g, All: 355 g			
Waterproof	IP67 For Housing	I	Null	
Operating Condition	Temp.:-25°C to +55°C, Humidity<95%			
Housing Color	Khaki Default, Optional Color By Order Quantity			

> Specifications are subject to change without prior notice

acking List:		Connection:
Camera	1	+12V – 1 , 4 – VIDEO VIDEO – 1 , 2 –
Instruction manual	1	$GND = 2 \bigcirc 3 = AUDIO + 12V = 3 \Box 4 =$
Self-Drilling Screw	4	Δ — 14mm Φ — 9.8mm
Mounting Plug	4	
roduct Size:		Installation Holes: